



Geotextile for reinforcement of Polyurea Rayston applications


DESCRIPTION AND APPLICATIONS



Geomax Spray 200 is a non-woven fabric of polypropylene fibers punched on one side and thermally calendered on the other.

This fabric exhibits high mechanical resistance and has been designed as a support for Rayston Polyurea applications, forming a high-resistance waterproofing composite.

In black tourmalite to facilitate control of the application of the projected product. Available in adhesive and non-adhesive versions.



Calendered surface

Uncalendered surface

TECHNICAL DATA

PRODUCT INFORMATION AND APPLICATION GUIDELINES

Composition	Polypropylene fibre
Thickness mm	2.5
Tensile strength, Kn	11.2/14.4
Longitudinal/transversal	
Elongación	67/80
Longitudinal/transversal	
Indentation resistance Kn	2.39
Thermal resistance:	-15°C to 80°C
Relevant standards	UNE EN-ISO 10319:2008, 12236:2007, 13433:2007
Packaging	Adhesive version: 1,50 m x 30 m rolls Non-adhesive version: 1,50 m x 70 m rolls
Storage	Keep away from sunlight and moisture. Use before 24 months after manufacturing date

INSTRUCTIONS FOR USE

Unroll the product over the surface and cut using suitable tools. Apply Rayston Polyurea according to the instructions in its technical data sheet.

USE RECOMMENDATIONS

Overlap contiguous rolls of Geomax Spray 200 at least 10 cm. For greater productivity, it is recommended to overlap the fabric, forming large cloths, and then spray the Rayston polyurea continuously on a large surface

ENVIRONMENTAL PRECAUTIONS

Geomax Spray 200 es residuo inerte. Gestionar de acuerdo con la legislación local.

OTHER INFORMATION

The information contained in this Technical Data Sheet, as well as our advice, both written as verbal or provided through testing, are based on our experience, and they do not constitute any product guarantee for the installer, who must consider them as simple information.

We recommend to study deeply all information provided before proceeding to the use or application of any of our products, and strongly advise to conduct tests "on-site" in order to determine their convenience for a specific project.

Our recommendations do not exempt of the obligation of installers to deeply study the right application method for these systems before use, as well as to conduct as many preliminary tests as possible should any doubt arise.

The application, use and processing of our products are beyond our control, and therefore under the exclusive responsibility of the installer. In consequence, the installer will be the only responsible of any damage derived from the partial or total in-observation of our indications, and in general, of the inappropriate use or application of these materials.

This Data Sheet supersedes all previous versions