

RUBBER MAT RUBBER MAT PLUS

RAYSTON
products



Recycled rubber crumb sheet

DESCRIPTION

Rubber Mat and Rubber Mat Plus are sheets of recycled rubber crumb bonded with a polyurethane resin. They make an excellent buffer base for ict absorption, especially in sport flooring. Certified to EN14904.

They are used in the Paviflex Sport System, suitable for:

- Hospitals
- Gyms
- Schools
- Commercial areas
- Offices
- Showrooms
- Multi-purpose recreational areas.

TECHNICAL DATA

INFORMATION ON THE PRODUCT BEFORE APPLICATION

	Rubber mat	Rubber mat plus																																				
Chemical description	SBR rubber agglomerate	SBR rubber agglomerate																																				
Colour	Black	Black																																				
Hardness (shore)	55A	45A																																				
Density	0,8 g/cm3	0,6 g/cm3																																				
Packaging	1.5 m width rolls Roll weight: 144 to 151 kg each	1.5 m width rolls Roll weight: 108 to 113 kg each																																				
	<table><thead><tr><th>Thickness (mm)</th><th>Length (m)</th></tr></thead><tbody><tr><td>3</td><td>40</td></tr><tr><td>4</td><td>30</td></tr><tr><td>5</td><td>24</td></tr><tr><td>6</td><td>20</td></tr><tr><td>7</td><td>17</td></tr><tr><td>8</td><td>15</td></tr><tr><td>9</td><td>14</td></tr><tr><td>10</td><td>12</td></tr><tr><td>12</td><td>10</td></tr></tbody></table>	Thickness (mm)	Length (m)	3	40	4	30	5	24	6	20	7	17	8	15	9	14	10	12	12	10	<table><thead><tr><th>Thickness (mm)</th><th>Length (m)</th></tr></thead><tbody><tr><td>4</td><td>30</td></tr><tr><td>5</td><td>24</td></tr><tr><td>6</td><td>20</td></tr><tr><td>7</td><td>17</td></tr><tr><td>8</td><td>15</td></tr><tr><td>9</td><td>14</td></tr><tr><td>10</td><td>12</td></tr></tbody></table>	Thickness (mm)	Length (m)	4	30	5	24	6	20	7	17	8	15	9	14	10	12
Thickness (mm)	Length (m)																																					
3	40																																					
4	30																																					
5	24																																					
6	20																																					
7	17																																					
8	15																																					
9	14																																					
10	12																																					
12	10																																					
Thickness (mm)	Length (m)																																					
4	30																																					
5	24																																					
6	20																																					
7	17																																					
8	15																																					
9	14																																					
10	12																																					
Storage	Keep at temperatures below 35°C, away from sunlight. Avoid contact with oils, solvents, petrol or related products.																																					
Use before	Use before 24 months after manufacturing date.																																					

APPLICATION INFORMATION

Please refer to the Paviflex Sport System information for specific guidance

SAFETY

Always consult information provided in the Safety Data Sheet of this product.

OTHER INFORMATION

The information contained in this DATA SHEET, as well as our advice, both written as verbal or provided through testing, are based on our experience, and they do not constitute any product guarantee for the installer, who must consider them as simple information.

We recommend to study deeply all information provided before proceeding to the use or application of any of our products, and strongly advise to conduct tests "on-site" in order to determine their convenience for a specific project.

Our recommendations do not exempt of the obligation of installers to deeply study the right application method for these systems before use, as well as to conduct as many preliminary tests as possible should any doubt arise. The application, use and processing of our products are beyond our control, and therefore under the exclusive responsibility of the installer. In consequence, the installer will be the only responsible of any damage derived from the partial or total in-observation of our indications, and in general, of the inappropriate use or application of these materials.

This data sheet supersedes previous versions.



KRYPTON CHEMICAL SL

C/ Martí i Franquès, 12 - Pol. Ind. les Tàpies
43890 - l'Hospitalet de l'Infant - Spain
Tel: +34 977 822 245 - Fax: +34 977 823 977

www.kryptonchemical.com - rayston@kryptonchemical.com

Latest update: 08/05/2020

Page: 1/1