

Aliphatic UV Waterproofing with Pending BBA

PRIMERS

	DRUM SIZE	COVER RATE
PU PRIMER	4 KG	75 GMS PER SQ.M
PU PRIMER	20 KG	75 GMS PER SQ.M
POROSITY SEALER FLEX	4 KG	200 GMS PER SQ.M
POROSITY SEALER FLEX	20 KG	200 GMS PER SQ.M
HUMIDITY PRIMER	5 KG	250 GMS PER SQ.M
HUMIDITY PRIMER	18 KG	250 GMS PER SQ.M
PU ZN PRIMER	11.5 KG	400 GMS PER SQ.M

WATERPROOFING

PRODUCT NAME

Impermax A QC (Impermax QC)	25kg	1.4KG PER SQ.M
Impermax A aliphatic (Impermax A)	25kg	600 GMS PER SQ.M

Glass Fibre Reinforcement

150 SQ.M ROLL ROLL 150M X 1M WIDE

SOLVENT	20 KG	50 GMS PER SQ.M
	4KG	50 GMS PER SQ.M

READ APPLICATION MANUAL

COVER PER DRUM

APPLICATION USE

53 SQ.M

PVC, METAL, EPDM, GLASS, GRP

266 SQ.M

PVC, METAL, EPDM, GLASS, GRP

20 SQ.M

DRY WOOD/ CONCRETE/BITUMEN FELT

100 SQ.M

DRY WOOD/ CONCRETE/BITUMEN FELT

20 SQ.M

DAMP WOOD, DAMP CONCRETE

72 SQ.M

DAMP WOOD, DAMP CONCRETE

28 SQ.M

RUSTY METAL

17.5 SQM PER DRUM

BASE LAYER OF 1.4KG WATERPROOFING

41 SQ.M PER DRUM

UV TOP COAT 0.6KG ALIPHATIC WATERPROOFING

SO USE lower cost IM-MAX (impermax) for Base Coat

150M X 1M

EMBEDDED IN BASE COAT OF WATERPROOFING

400 SQ.M

CLEANING AND SOLVENT WIPE

80 SQ.M

CLEANING AND SOLVENT WIPE