

BBA LIQUID WATERPROOFING Impermax qc 20 Year Warranty

PRIMERS

PRODUCT NAME	DRUM SIZE	COVER RATE
PU PRIMER	4KG	75GMS PER SQM
PU PRIMER	20KG	75GMS PER SQM
POROSITY SEALER FLEX	4KG	200GMS PER SQM
POROSITY SEALER FLEX	20KG	200GMS PER SQM
HUMIDITY PRIMER	5KG	250GMS PER SQM
HUMIDITY PRIMER	18KG	250GMS PER SQM
PU ZN RUST PRIMER	11.5KG	400GMS PER SQM

WATERPROOFING

PRODUCT NAME	DRUM SIZE	COVER RATE
Impermax QC	10kg	2kg per sqm
Impermax QC	25kg	2kg per sqm

GLASS FIBRE REINFORCEMENT 150 SQM ROLL ROLL-150M X 1M WIDE

APPLICATION MANUAL -PLEASE READ APPLICATION MANUAL TO ENSURE CORRECT

SOLVENT	20KG	50 GMS PER SQ.M
	4KG	50 GMS PER SQ.M

Highest Fire Rating in Europe

COVER PER DRUM	APPLICATION USE
53 SQ.M	PVC, METAL, EPDM, GLASS, GRP
266 SQ.M	PVC, METAL, EPDM, GLASS, GRP
20 SQ.M	DRY- WOOD/CONCRETE, BITUMEN
100 SQ.M	DRY- WOOD/CONCRETE, BITUMEN
20 SQ.M	DAMP WOOD , DAMP CONCRETE
72 SQ.M	DAMP WOOD , DAMP CONCRETE
28 SQ.M	RUSTY METAL

COVER PER DRUM	APPLICATION USE
10sqm of 1 x layer at 1kg	Base layer of 1kg then top coat of 1kg
25sqm of 1 x layer at 1kg	Base layer of 1kg then top coat of 1kg
150M X 1M WIDE	EMBEDDED BETWEEN 2 X LAYER OF WATERPROOFING
INSTALLATION	
400 SQ.M PER DRUM	CLEANING AND FOR SOLVENT WIPE
80 SQ.M PER DRUM	CLEANING AND FOR SOLVENT WIPE